





Series 194

HYD XW

1450rpm



AR_s194-13_v01

13/05/2023



Series 194

HYD XW

1450rpm

P	Code	Description	Q	Note	Validity
1	1949203	Head assembly	Ø 22	1	
2	1941210	Head		1	
3	1140300	Plug	3/4" G	1	C=35Nm
4	550350	O-ring	Ø 23,81x2,62	1	
5	1980740	Plug	3/8" G brass	1	C=20Nm
6	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54
9	1940140	Plug		6	
10	1940150	Ring	anti-extrusion	6	
11	1949050	Complete valve		6	
12	1140450	O-ring	Ø 20,24x2,62	12	Lubricate with grease Molykote PG54
20	1940270	Gasket	Ø 22	3	Lubricate with grease Molykote PG54
22	1940200	Piston guide	front Ø 22	3	
23	1940480	Gasket	Ø 22	3	Lubricate with grease Molykote PG54
24	1941220	O-ring	cut Ø 22	3	>I 26/22
24	2283660	O-ring	cut Ø 22	3	I> 27/22
25	1940460	Piston guide	rear Ø 22	3	>I 26/22
25	1944630	Piston guide	rear Ø 22	3	I> 27/22
26	820490	O-ring	Ø 34,65x1,78	3	
27	1940560	Ring	seal	3	
40	1941330	Pump body		1	
41	1940260	Screw	TCEI M10x80	8	C=50Nm
42	650530	Washer		8	
43	1140370	Plug		1	
44	1980740	Plug	3/8" G brass	1	C=20Nm
45	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54
46	1940410	O-ring	Ø 132x3	1	
47	1200430	Screw	TCEI M6x16	6	Screw with Loxeal 55-14 / C=10Nm
50	1940570	Nut		3	Screw with Loxeal 55-14 / C=20Nm
51	1940580	Washer		3	
52	1420120	Piston	Ø 22	3	
53	880840	O-ring	Ø 9,25x1,78	3	Lubricate with grease Molykote G807
54	1940120	Ring	anti-extrusion	3	
55	960460	Plate		3	
56	1940070	Piston	guide	3	
57	1940060	Pin		3	
58	1940051	Connecting-rod	aluminium	3	Lubricate with grease Molykote BR2 PLUS / C=20Nm
65	1949010	Cover	complete	1	
66	1260430	Ring		1	

P	Code	Description	Q	Note	Validity
67	1780690	Plate		1	
68	1260250	Level gauge		1	
69	1140450	O-ring	Ø 20,24x2,62	1	Lubricate with grease Molykote PG54
70	740290	O-ring	Ø 14x1,78	1	Lubricate with grease Molykote PG54
71	1980740	Plug	3/8" G brass	1	C=20Nm
75	1140410	Bearing		2	
76	1941380	O-ring	Ø 66,34x2,62	2	
77	1949011	Cover		1	
79	1941290	Ring		1	
80	1941260	Plate		1	
81	1941270	Level gauge		1	
82	100410	O-ring	Ø 34,6x2,62	1	
83	1941390	Shim 0.05mm		1	
83	1941400	Shim 0.10mm		1	
83	1941410	Shim 0.19mm		1	
83	1941420	Shim 0.25mm		1	
84	850370	Screw	TCEI M8x16	4	C=24,5Nm
85	1942050	Shaft	1 marked	1	
90	1941240	Support		1	
91	820681	Ring	seal	1	Screw with Loxeal 55-14 / C=10Nm
94	1780430	Ring		1	
97	200231	Washer		4	
98	1940370	Foot		2	
99	1940380	Screw	TCEI 10x18	4	C=50Nm
A	2780	Valve kit		1	
B	1891	Piston kit	Ø 22	1	
C	2873	Oil seal kit		1	
E	2783	Water seal kit	Ø 22	1	
E	2779	Water seal kit	Ø 22 Viton	1	
H	2785	Piston guide kit	Ø 22	1	>I 26/22
H	47164	Piston guide kit	Ø 22	1	I> 27/22

Revision: 1

Oil type: SAE 15W40

Attachment:

Date: 13/05/2023

Oil quantity: 0,870 Kg

C=Tightening torque (Tolerance +0 ÷ -10%)

* = Not present for electric pump




Series 194

HYD XW

1450rpm

P	Code	Description		Q	Note	Validity
1	1383550	Flange	F38	1		
2	620610	Screw	TCEI M8x30	4	Screw with Loxeal 55-14 / C=24,5Nm	



F38

AR-1_000063_v01

Revision: 1

Oil type: SAE 15W40

Attachment:

Date: 13/05/2023

Oil quantity: 0,870 Kg

C=Tightening torque (Tolerance +0 ÷ -10%)

21606 - HYD XW 30.10 + F38




Series 194

HYD XW

1450rpm

P	Code	Description		Q	Note	Validity
1	4770	Motor	hydraulic	1		
2	540300	Screw	TCEI M10x30	2	C=50Nm	
3	900270	Washer		2		



AR_motore-12_v01

Revision: 1

Oil type: SAE 15W40

Attachment:

Date: 13/05/2023

Oil quantity: 0,870 Kg

C=Tightening torque (Tolerance +0 ÷ -10%)